## <sup>2024</sup> **KLX®300**







POWER		Front Brakes	Single 250mm petal disc with a dual-piston caliper
Engine	4-stroke single, DOHC, liquid-cooled	Rear Brakes	Single 240mm petal disc with single-piston caliper
Displacement	292cc		
Bore x Stroke	78.0 x 61.2mm	DETAILS	
Compression Ratio	11.1:1	Frame Type	Tubular, Semi Double Cradle
Fuel System	DFI® with 34mm Keihin throttle body	Rake/Trail	26.7°/4.2 in
Ignition	CDI	Overall Length	85.6 in
Transmission	6-speed, return shift with wet multi-disc	Overall Width	32.3 in
	manual clutch	Overall Height	46.7 in
Final Drive	Chain	Ground	10.8 in
DEDEODUANOE		Clearance	
PERFORMANCE		Seat Height	35.2 in
Front	43mm inverted cartridge fork with adjustable	Curb Weight	302.1 lb*
Suspension / Wheel Travel	compression damping /10.0 in	Fuel Capacity	2.0 gal
Rear Suspension	Uni-Trak® gas charged shock with piggyback	Wheelbase	56.7 in
/ Wheel Travel	reservoir with adjustable compression, rebound damping and spring preload/9.1 in	Color Choices	Lime Green, Battle Gray, Cypher Camo Gray (Matte)

Rear Tire

3.00 x 21

4.6 x 18

**Front Tire** 

## Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

12 Month Limited Warranty

12, 24, 36, or 48 months

Warranty

Kawasaki

Protection Plus™ (optional)