2024 **MULE PRO-FXR[™] 1000 LE**









Fuel Capacity

Turning Radius

(LxWxH) **Cargo Bed Load**

Capacity

Lighting

Payload Capacity

Seating Capacity

Towing Capacity

DETAILS

Overall Length Overall Width

Overall Height

Cargo Bed Dimensions



7.9 gal

14.0 ft

3

2,000 lb

122.0 in

64.0 in

78.5 in

37.6 x 53.3 x 11.0 in

999 lb / 600.0 lb CA Model

1,616.3 lb / 1,263.5 lb CA Model

(2) Halogen headlights. (2) LED headlights

POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas
Displacement	999cc
Maximum Torque	61.5 lb-ft
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	10.1:1
Fuel System	DFI® with 38mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (L,H,N,R)
Final Drive	Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	90 amp

CAPABILITY

UAF ADILITT		Curb Weight	1,746.4 lb* / 1,748.6 lb* CA Model
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Wheelbase	79.7 in
Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil
Front Tires	27 x 9.00-12, radial		pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking
Rear Tires	27 x 11.00-12, radial		indicators, seatbelt reminder lamps
Steering	Electric Power Steering (EPS), Tilt steering	Wheel Type	Alloy
Front Brakes	Dual Disc, 2 piston caliper	Additional Features	Roof, Rear Bumper, Contoured Two-Tone Bench Seat, Additional Cup Holders
Rear Brakes	Dual Disc, 1 piston caliper		
Park Brake Type	Independent, Mechanical Disc	Color Choices	Ice Gray
Ground Clearance	13.2 in (max), 12.2 in (std)	Warranty	Kawasaki STRONG 3-Year Limited Warranty
		Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE[™] side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

