## <sup>2021</sup> KLX®140R







## Front Brakes Single 220mm petal disc with a dual-piston POWER caliper **Rear Brakes** Single 186mm petal disc with single-piston 4-stroke single, SOHC, air-cooled Engine caliper Displacement 144cc **DETAILS Bore x Stroke** 58.0 x 54.4mm Compression 9.5:1 **Frame Type** High-tensile steel, box-section perimeter Ratio 27°/3.3 in Rake/Trail 20mm Keihin carburetor **Fuel System** 71.7 in **Overall Length** Ignition Digital DC-CDI **Overall Width** 31.1 in Transmission 5-speed, return shift, with wet multi-disc manual clutch **Overall Height** 41.3 in **Final Drive** Chain Ground 9.3 in Clearance PERFORMANCE **Seat Height** 30.7 in **Curb Weight** 205.0 lb\* 33mm telescopic fork/7.1 in Front Suspension / **Fuel Capacity** 1.5 gal Wheel Travel Wheelbase 49.6 in Uni-Trak<sup>®</sup> linkage system and single shock Rear with 5-way preload adjustability/7.1 in Suspension / **Color Choices** Lime Green Wheel Travel Warranty 6 Months **Front Tire** 70/100-17 Kawasaki 12, 24, or 36 months **Rear Tire** 90/100-14 Protection Plus™

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

(optional)