## **MULE PRO-FXT™ EPS LE**





MSRP **\$16,299** 



SUPER BLACK



FIRECRACKER RED



7.9 gal

16.0 ft

models)

1616 lb

64.0 in

## **POWER**

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

**Alternator Output** 

75 amp

(max)

Seating Capacity

**Fuel Capacity** 

**Turning Radius** 

**Cargo Bed Load** 

**Payload Capacity** 

Cargo Bed Dimensions (LxWxH)

Capacity

3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights. (2) LED headlights

## CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial 26x11.00-12, radial

Rear Tires

Electric Power Steering (EPS), Tilt steering

Front Brakes

Steering

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type

Independent, Mechanical Disc

**Ground Clearance** 

10.2 in

## DETAILS

Overall Length 133.3 in

Overall Width

Overall Height 79.5 in

Curb Weight 1922.8 lb\*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-person)

1000 lb (3-person)350 lb (6-person)(600 lb for California

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type Alloy

Color Choices Super Black, Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection Plus™ (optional) 12, 24 or 36 months

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.