MULE PRO-FXT™ RANCH EDITION





\$17,299



METALLIC PHANTOM SILVER



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio

Fuel System DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

Selectable 2WD/4WD, shaft. Dual mode rear differential with **Final Drive**

differential lock

Engine Braking

Alternator Output

(max)

75 amp

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type

Independent, Mechanical Disc

Ground Clearance 10.0 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Dimensions (LxWxH)

Cargo Bed Load

Capacity

1000 lb (3-person)350 lb (6-person)(600 lb for California

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-person)

models)

Payload Capacity 1574 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity

Lighting (2) Halogen headlights. (2) LED headlights

DETAILS

135.6 in **Overall Length Overall Width** 64.0 in **Overall Height** 79.5 in **Curb Weight** 1971.3 lb*

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Wheel Type Alloy

Color Choices Metallic Phantom Silver

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection Plus™ (optional)

12, 24 or 36 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.