

2021

TERYX KRX<sup>®</sup> 1000 eS


Kawasaki

Let the Good Times Roll<sup>®</sup>



MSRP


\$24,399

 METALLIC ONYX BLACK



POWER		DETAILS	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Payload Capacity	781 lbs
Displacement	999cc	Seating Capacity	2
Maximum Torque	76.7 lb-ft @ 7000 rpm	Towing Capacity	N/A
Bore x Stroke	92.0 x 75.1 mm	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight
Compression Ratio	11.5:1	Standard Ground Clearance/Maximum Ground Clearance†	14.0 in / 14.4 in
Fuel System	DFI with two 50mm throttle bodies	FRAME	
Ignition	TCBI with electronic advance		
Starting System	Electric	Frame	Ladder type, tubular steel
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Overall Length	132.1 in
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Width	68.1 in
Engine Braking	Yes	Overall Height	77.0 in
CAPABILITY		Curb Weight	1944.8 lbs (1947.0 CA)*
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in.	Wheelbase	98.8 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in.	Instruments	Multi-function digital meter with high-grade full-color TFT LCD screen that offers three selectable display modes (Digital, Analogue, Simple) and can auto adjust screen brightness to suit available light. Display functions include speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), driving mode (2WD/4WD/4WD+Diff Lock), power mode (Full/Low), suspension mode (Soft/Normal/Firm), clock, CVT temperature, digital tachometer, odometer, dual trip meters, total time, trip time, average speed, water temperature, battery voltage, Bluetooth indicator**, telephone call indicator, main indicator, economical riding indicator, maintenance reminder, neutral indicator, reverse indicator, headlight high-beam indicator, battery warning lamp, EPS warning lamp, CVT belt warning lamp, seatbelt warning lamp, parking indicator lamp, oil warning lamp, water temperature warning lamp, engine check lamp.
Front Tires	MAXXIS Carnivore 31 x 10.00R15 8PR	Wheel Type	Alloy with bead-lock wheels
Rear Tires	MAXXIS Carnivore 31 x 10.00R15 8PR	Color Choices	Metallic Onyx Black
Steering	Electric Power Steering (EPS) / rack-and-pinion	Warranty	6 months
Front Brakes	Dual hydraulic discs with two-piston calipers	Kawasaki Protection Plus™ (optional)	12, 24, or 36 months
Rear Brakes	Dual hydraulic discs with single-piston calipers	WARRANTY	
Fuel Capacity	10.6 gal		
Turning Radius	20.3 ft		
Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in		
Cargo Bed Load Capacity	351 lbs		

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

†Maximum ground clearance is measured at maximum pre-load suspension setting.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx<sup>®</sup> side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.