## TERYX4™ S CAMO





\$16,999



REALTREE XTRA® GREEN CAMO



## **POWER**

**Engine** 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

**Displacement** 783cc

**Maximum Torque** 47.0 lb-ft@ 5500 rpm

**Bore x Stroke** 85.0 x 69.0mm

**Compression Ratio** 10.7:1

**Fuel System** DFI® with two 36mm Mikuni throttle bodies

TCBI with electronic advance Ignition

**Starting System** Electric

**Transmission** Automatic CVT with centrifugal clutch (H,L,N,R)

**Final Drive** Selectable 2WD/4WD with locking front differential, shaft

**Engine Braking** 

**Fuel Capacity** 7.9 gal

**Turning Radius** 17.7 ft.

**Cargo Bed** 

**Dimensions (LxWxH)** 

17.9 x 47.6 x 8.7 in

**Cargo Bed Load** Capacity

249 lh

**Payload Capacity** 

1096 lb

**Seating Capacity** 

**Towing Capacity** 1300 lb

(4) LED headlights, (2) LED taillights, LED stoplight Lighting

**Standard Ground** 

Clearance/Maximum **Ground Clearancet** 

11.2 in / 12.2 in

## **DETAILS**

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping / 10.7 in.

**Rear Suspension / Wheel Travel** 

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping / 10.0 in.

**Front Tires** Maxxis 27 x 9-14

**Rear Tires** Maxxis 27 x 11-14

Electric Power Steering (EPS) / rack-and-pinion Steering

**Front Brakes** Dual hydraulic discs with two-piston calipers

**Rear Brakes** Sealed, oil-bathed, multi-disc

Steel Tube Double-X Reinforcement Frame

**Overall Length** 125.4 in

**Overall Width** 62.6 in

**Overall Height** 80.5 in

**Curb Weight** 1642.7 lb\*

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and

parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

**Wheel Type** 

**Color Choices** Realtree Xtra® Green Camo

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). †Maximum ground clearance is measured at maximum pre-load suspension setting.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.