## <sup>2021</sup> TERYX4<sup>™</sup>





MSRP **\$15,999** 



VIBRANT BLUE



## **POWER**

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft@ 5500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with two 36mm Mikuni throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Ground Clearance 11.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.7 ft

Cargo Bed 17.9 x 47.6 x 8.7 in Dimensions (LxWxH)

Cargo Bed Load 249 lb

Capacity

Payload Capacity 1109 lb

Seating Capacity 4

Towing Capacity 1300 lb

**Lighting** (2) headlights, (2) taillights, LED stoplight

## **CAPABILITY**

Front Suspension / Wheel Travel

Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in.

Rear Suspension / Wheel Travel

Double Wishbone; Fox Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.3 in.

Front Tires Maxxis 26 x 9-12

Rear Tires Maxxis 26 x 11-12

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

## **DETAILS**

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in
Overall Width 60.0 in

Overall Height 77.8 in

Curb Weight 1605.2 lb\*

Wheelbase 85.6 in

**Instruments** Multi-function digital meter with speedometer, fuel gauge,

clock, hour meter, odometer, dual trip meter and parkingbrake indicator, R/N/P/4WD, water temp and low-oil-

pressure indicators

Wheel Type Steel

Color Choices Vibrant Blue

Warranty Kawasaki Strong 3-Year Limited Warranty

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warnings: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.