
2021 **VULCAN[®] S ABS**







| POWER | | Front Tire | 120/70x18 |
|--------------------|--|-----------------------|--|
| | | Rear Tire | 160/60x17 |
| Engine | 4-stroke, 2-cylinder, DOHC, liquid-cooled | Front Brakes | Single 300mm disc with twin-piston |
| Displacement | 649cc | | caliper |
| Bore x Stroke | 83.0 x 60.0mm | Rear Brakes | Single 250mm disc with single-piston caliper |
| Compression | | | · |
| Ratio | | DETAILS | |
| Maximum | 46.3 lb-ft @ 6600 rpm | | |
| Torque | | Frame Type | High-tensile steel diamond frame |
| Fuel System | DFI 38mm Throttle Bodies (2), with sub- throttle valves | Overall Length | 90.9 in |
| Ignition | TCBI w/ Electronic Advance | Overall Width | 34.6 in |
| - | | Overall Height | 43.3 in |
| Transmission | 6-speed with positive neutral finder | Ground | 5.1 in |
| Final Drive | Sealed Chain | Clearance | 3.1 11 |
| PERFORMANCE | | Seat Height | 27.8 in |
| | | Curb Weight | 498.3 lb* |
| Front | 41mm telescopic fork/5.1 in | J J | |
| Suspension / | | Fuel Capacity | 3.7 gal |
| Wheel Travel | | Wheelbase | 62.0 in |

Rear Suspension / Wheel Travel

Scan with camera

to view videos,

key features

and more.

Lay-down offset rear shock with linkage and adjustable preload/3.1 in

> *Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Metallic Flat Raw Graystone, Pearl

Blizzard White

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Color Choices

Specifications subject to change. Visit Kawasaki.com for full product details.