

2022

KLX®110R L



MSRP
\$2,699



POWER

| | |
|-------------------|--|
| Engine | 4-stroke single, SOHC, air-cooled |
| Displacement | 112cc |
| Bore x Stroke | 53.0 x 50.6mm |
| Compression Ratio | 9.5:1 |
| Fuel System | 18mm Keihin carburetor and screw type throttle limiter on grip housing |
| Ignition | DC-CDI |
| Transmission | 4-speed, return shift, wet multi-disc manual clutch |
| Final Drive | Chain |

PERFORMANCE

| | |
|---------------------------------|---|
| Front Suspension / Wheel Travel | 30mm hydraulic telescopic fork/5.5 in |
| Rear Suspension / Wheel Travel | Swingarm with single hydraulic shock/5.2 in |
| Front Tire | 2.50x14 |
| Rear Tire | 3.00x12 |

| | |
|--------------|--------------------------------------|
| Front Brakes | 90mm mechanical drum, cable actuated |
| Rear Brakes | 110mm mechanical drum, rod actuated |

DETAILS

| | |
|--------------------------------------|------------------------------------|
| Frame Type | Backbone frame, high-tensile steel |
| Rake/Trail | 24.2° / 1.9 in |
| Overall Length | 61.4 in |
| Overall Width | 25.6 in |
| Overall Height | 39.0 in |
| Ground Clearance | 10.4 in |
| Seat Height | 28.7 in |
| Curb Weight | 167.5 lb* |
| Fuel Capacity | 1.0 gal |
| Wheelbase | 42.3 in |
| Color Choices | Lime Green |
| Warranty | 6 Months |
| Kawasaki Protection Plus™ (optional) | 12, 24, or 36 months |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.