²⁰²² **KLX®110R**







POWER

Engine	4-stroke single, SOHC, air-cooled	
Displacement	112cc	
Bore x Stroke	53.0 x 50.6mm	
Compression Ratio	9.5:1	
Fuel System	18mm Keihin carburetor and screw type throttle limiter on grip housing	
Ignition	DC-CDI	
Transmission	4-speed, return shift, automatic centrifugal and wet, multi-disc clutch	
Final Drive	Chain	

Front Tire2.50x14Rear Tire3.00x12Front Brakes90mm mechanical drum, cable actuatedRear Brakes110mm mechanical drum, rod actuated

DETAILS

and screw type ousing	Frame Type	Backbone frame, high-tensile steel
	Rake/Trail	24.8°/2.0 in
	Overall Length	61.4 in
comatic ti-disc clutch	Overall Width	25.6 in
	Overall Height	37.6 in
	Ground Clearance	8.5 in
oic fork/4.3 in	Seat Height	26.8 in
	Curb Weight	167.5 lb*
draulic	Fuel Capacity	1.0 gal
	Wheelbase	42.3 in
	Color Choices	Lime Green

PERFORMANCE

Front Suspension / Wheel Travel 30mm hydraulic telescopic fork/4.3 in

Rear Suspension / Wheel Travel Swingarm with single hydrauli shock/4.3 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.