²⁰²² KLX®140R L







Front Brakes Single 220mm petal disc with a dual-piston POWER caliper **Rear Brakes** Single 186mm petal disc with single-piston 4-stroke single, SOHC, air-cooled Engine caliper Displacement 144cc **DETAILS Bore x Stroke** 58.0 x 54.4mm Compression 9.5:1 **Frame Type** High-tensile steel, box-section perimeter Ratio 27°/3.8 in Rake/Trail 20mm Keihin carburetor **Fuel System** 74.6 in **Overall Length** Ignition Digital DC-CDI **Overall Width** 31.1 in 5-speed, return shift, with wet multi-disc Transmission manual clutch **Overall Height** 42.3 in **Final Drive** Chain Ground 10.0 in Clearance PERFORMANCE **Seat Height** 31.5 in **Curb Weight** 209.4 lb* 33mm telescopic fork/7.1 in Front Suspension / **Fuel Capacity** 1.5 gal Wheel Travel Wheelbase 50.6 in Uni-Trak[®] linkage system and single shock Rear with piggyback reservoir, fully adjustable Suspension / **Color Choices** Lime Green Wheel Travel preload and 22-way rebound damping/7.1 in 6 Months Warranty **Front Tire** 70/100-19 Kawasaki 12, 24, or 36 months **Rear Tire** 90/100-16 Protection Plus™ (optional)



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.