







LIME GREEN



POWER

Engine 2-stroke single with exhaust power valve (KIPS), liquid-cooled

9.9:1 (Low speed)/8.6:1 (High speed)

Displacement 112cc

Bore x Stroke 52.5 x 51.6mm

Compression Ratio

Fuel System 28mm Keihin carburetor

Ignition CDI with digital advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Single 220mm petal disc with dual-piston

caliper

Rear Brakes

Single 184mm petal disc with single-piston

caliper

DETAILS

Frame Type High-tensile steel perimeter design withsubframe member

Rake/Trail 29°/4.3 in

Overall Length 75.6 in

Overall Width 30.1 in

Overall Height 45.3 in

Ground

Clearance

13.0 in

Seat Height 34.3 in

Curb Weight 169.7 lb*

Fuel Capacity 1.32 gal

Wheelbase 51.6 in

Color Choices Lime Green

Warranty Not Available

Kawasaki Protection Plus™ (optional) Not Available

PERFORMANCE

Front
Suspension /
Wheel Travel

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring

preload/10.8 in

Front Tire

70/100-19

Rear Tire

90/100-16



