









POWER

Engine 2-stroke single with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression 10.9:1 (low speed) - 9.0:1 (high speed)

Ratio

Fuel System 28mm Keihin carburetor

Ignition CDI with digital advance

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Single 220mm petal disc with dual-piston

caliper

Rear Brakes

Single 184mm petal disc with single-piston

caliper

DETAILS

Frame Type High-tensile steel perimeter design with subframe member

Rake/Trail 29°/3.8 in

Overall Length 72.0 in

Overall Width 30.1 in

Overall Height 43.3 in

Ground 11.4 in Clearance

Seat Height 32.7 in

Curb Weight 165.3 lb*

Fuel Capacity 1.32 gal

Wheelbase 49.8 in

Color Choices Lime Green

Warranty Not Available

Kawasaki Not Available Protection

PERFORMANCE

Front
Suspension /
Wheel Travel

36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in

Rear Suspension / Wheel Travel

Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in

Front Tire

70/100-17

Rear Tire

90/100-14

Scan with camera to view videos, key features and more.



Plus™ (optional)