

2022

MULE™ 4010 TRANS4x4® FE

Kawasaki

Let the Good Times Roll®

MSRP

\$12,399

BRIGHT WHITE



POWER

| | |
|-------------------------|---|
| Engine | 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled |
| Displacement | 617cc |
| Maximum Torque | 34.7 lb-ft @ 2500 rpm |
| Bore x Stroke | 2.99x2.68 in |
| Compression Ratio | 10:3:1 |
| Fuel System | DFI® with 34mm Mikuni throttle body |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking | No |
| Alternator Output (max) | 23 amp |

CAPABILITY

| | |
|---------------------------------|-------------------------------|
| Front Suspension / Wheel Travel | MacPherson Strut/3.9 in |
| Rear Suspension / Wheel Travel | DeDion Axle/2.8 in |
| Front Tires | 23x11.00-10 |
| Rear Tires | 23x11.00-10 |
| Steering | Electric Power Steering (EPS) |
| Front Brakes | Drum |
| Rear Brakes | Drum |
| Park Brake Type | Independent, Mechanical Drum |

| | |
|------------------------------|--|
| Ground Clearance | 7.1 in |
| Fuel Capacity | 6.3 gal |
| Turning Radius | 12.8 ft |
| Cargo Bed Dimensions (LxWxH) | 50.4 x 47.6 x 11.2 in (2-person), 30.3 x 47.6 x 11.2 in (4-person) |
| Cargo Bed Load Capacity | 800 lb (2-person), 401 lb (4-person) |
| Payload Capacity | 1330 lb |
| Seating Capacity | 2-4 |
| Towing Capacity | 1200 lb |
| Lighting | (2) Halogen headlights (2) tail/brake lights |

DETAILS

| | |
|---------------------|---|
| Overall Length | 128.5 in |
| Overall Width | 58.5 in |
| Overall Height | 78.1 in |
| Curb Weight | 1614.1 lb* |
| Wheelbase | 85.2 in |
| Instruments | Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet, fuel gauge, hour meter |
| Wheel Type | Steel |
| Additional Features | Roof, Horn, Universal Key, High Visibility Orange Seatbelts |
| Color Choices | Bright White |

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ 4000/4010 and MULE 4000/4010 TRANS™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.