MULE PRO-DXT™ DIESEL





\$16,699



SUPER BLACK



POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement

38.3 lb-ft @ 2400 rpm **Maximum Torque**

Bore x Stroke 2.91x3.03 in

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking

Alternator Output 55 amp

(max)

Ground Clearance 10.2 in **Fuel Capacity** 7.9 gal

Turning Radius 16.0 ft

Cargo Bed **Dimensions (LxWxH)**

999 lb (3-person), 350 lb (6-person) **Cargo Bed Load**

Capacity

1581 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity

Payload Capacity

Lighting (2) Halogen headlights.

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone / 8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12 **Rear Tires** 26x11.00-12

Steering Rack-and-pinion, Tilt steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Park Brake Type Independent, Mechanical Disc

DETAILS

Overall Length 133.3 in **Overall Width** 64.0 in

Overall Height 77.6 in

Curb Weight 1922.8 lb*

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT warning indicator, neutral, reverse and parking indicators,

42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-person)

seatbelt reminder lamps

Wheel Type Steel

Color Choices Super Black

Kawasaki Strong 3-Year Limited Warranty Warranty

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471