## **MULE PRO-FX™ EPS LE**





\$15,599



FIRECRACKER RED



## **POWER**

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Maximum Torque** 48.0 lb-ft @ 3500 rpm

2.83x2.62 in **Bore x Stroke** 

**Compression Ratio** 9.5:1

DFI® with 34mm throttle body **Fuel System** 

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission** 

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** Yes

**Alternator Output** 

(max)

75 amp

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone/8.7 in

Rear Suspension /

Double wishbone/8.5 (L) /8.7 (R) in

Wheel Travel

26x9.00-12, radial

**Rear Tires** 

26x11.00-12, radial

Steering

**Front Tires** 

Electric Power Steering (EPS), Tilt steering

**Front Brakes** 

Dual Disc, 2 piston caliper

**Rear Brakes** 

Dual Disc, 1 piston caliper

**Park Brake Type** 

Independent, Mechanical Disc

**Ground Clearance** 

10.4 in

**Fuel Capacity** 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed

**Dimensions (LxWxH)** 

54.1 x 53.3 x 11.0 in

**Cargo Bed Load** 

Capacity

999 lb (600.0 lb for California models)

1616.3 lb (1263.5 for California models)

**Payload Capacity** 

3

**Seating Capacity Towing Capacity** 

2000 lb

1832.4 lb\*

Lighting

(2) Halogen headlights. (2) LED headlights

## **DETAILS**

**Overall Length** 133.3 in **Overall Width** 64.0 in

**Overall Height** 79.7 in

Wheelbase 92.3 in

Instruments

**Curb Weight** 

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

**Wheel Type** Alloy

**Color Choices** Firecracker Red

Warranty Kawasaki Strong 3-Year Limited Warranty

**Kawasaki Protection** 

Plus™ (optional)

12, 24 or 36 months

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.