MULE PRO-FX™





\$13,699



SUPER BLACK



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.4 in **Fuel Capacity** 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load Capacity

999 lb (600.0 lb for California models)

54.1 x 53.3 x 11.0 in

Payload Capacity 1616.3 lb (1263.5 for California models)

Seating Capacity

Towing Capacity 2000 lb

Lighting (2) Halogen headlights.

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone / 8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial 26x11.00-12, radial **Rear Tires** Steering Rack-and-pinion

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Park Brake Type Independent, Mechanical Disc **DETAILS**

Overall Width

Overall Length 133.3 in

Overall Height 77.4 in

Curb Weight 1816.9 lb*

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

64.0 in

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices Super Black

Warranty Kawasaki Strong 3-Year Limited Warranty

Kawasaki Protection 12, 24 or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471