MULE PRO-FXT™ EPS CAMO





\$17,999



REALTREE XTRA® GREEN CAMO



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

2.83x2.62 in **Bore x Stroke**

Compression Ratio 9.5:1

DFI® with 34mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

75 amp

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes Park Brake Type Dual Disc, 1 piston caliper

Independent, Mechanical Disc

Ground Clearance

10.2 in

7.9 gal **Fuel Capacity**

Cargo Bed

42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

16.0 ft

Cargo Bed Load Capacity

Turning Radius

999 lb (3-person), 350 lb (6-person), (348 lb for California

models)

Payload Capacity

1616.3 lb (1263.5 for California models)

Seating Capacity

3-person (1 row), 6 person (2 row)

Towing Capacity

2000 lb

Lighting

(2) Halogen headlights. (2) LED headlights.

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1916.1 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices Realtree Xtra® Green Camo

Warranty Kawasaki Strong 3-Year Limited Warranty

Kawasaki Protection

Plus™ (optional)

12, 24 or 36 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.