# **MULE PRO-MX™**





### MSRP **\$11,199**



SUPER BLACK



#### **POWER**

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Park Brake Type Independent, Mechanical Disc

33.4 x 44.1 x 9.1 in

699 lb (600 lb California models)

**Ground Clearance** 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

city

Cargo Bed Load Capacity

Payload Capacity 1200 lb

Seating Capacity 2

Towing Capacity 1500 lb

Lighting (2) Halogen headlights

## **CAPABILITY**

Front Suspension / Double wishbone / 8.6 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

 Front Tires
 25x8.00-12, radial

 Rear Tires
 25x10.00-12, radial

Steering Rack & Pinion, Tilt steering

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

## **DETAILS**

Overall Length 110.0 in
Overall Width 60.0 in
Overall Height 74.4 in

Curb Weight 1578.8 lb\*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps

Wheel Type Steel

**Color Choices** Super Black

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.