

2022

NINJA H2® CARBON

Kawasaki
 Let the Good Times Roll®

 MSRP
\$34,000

 MIRROR COATED MATTE SPARK BLACK/
 CANDY FLAT BLAZED GREEN


POWER

Engine	Liquid -cooled, 4-stroke, In-Line Four, DOHC, 16-valve
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	8.5:1
Maximum Torque	104.9 lb-ft @ 11,000 rpm
Fuel System	DFI® with 50mm throttle bodies (4) with dual injection ; Kawasaki Supercharger
Ignition	Digital
Transmission	6-speed, return, dog-ring
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki Cornering Management Function (KCMF), Kawasaki Traction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in
---------------------------------	---

Rear Suspension / Wheel Travel	Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 24-way compression and rebound damping and adjustability and hand-turn spring preload adjustability, and top-out spring/5.3 in
Front Tire	120/70 ZR17 (58W)
Rear Tire	200/55 ZR17 (78W)
Front Brakes	Dual radial-mount, opposed 4-piston Brembo Stylema® calipers, dual semi-floating 330mm discs, KIBS ABS
Rear Brakes	Opposed 2-piston calipers, single 250mm disc, KIBS ABS

DETAILS

Frame Type	Trellis, high-tensile steel, with swingarm mounting plate
Rake/Trail	24.5° /4.1 in
Overall Length	82.1 in
Overall Width	30.3 in
Overall Height	44.3 in
Ground Clearance	5.1 in
Seat Height	32.5 in
Curb Weight	524.8 lb*
Fuel Capacity	4.5 gal
Wheelbase	57.3 in
Special Features	Rideology the App Smartphone Connectivity, all-LED lighting, Highly Durable Paint, TFT Instrumentation
Color Choices	Mirror Coated Matte Spark Black/Candy Flat Blazed Green

 Scan with camera
 to view videos,
 key features
 and more.


*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
 Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.