2022 VULCAN[®] S CAFE







POWER

		Rear Tire
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	
Displacement	649сс	Rear Brakes
Bore x Stroke	83.0 x 60.0mm	
Compression Ratio	10.8:1	DETAILS
Maximum Torque	46.3 lb-ft @ 6600 rpm	Frame Type
Fuel System	DFI 38mm Throttle Bodies (2), with sub- throttle valves	Rake/Trail
,		Overall Length
Ignition	TCBI w/ Electronic Advance	Overall Width
Transmission	6-speed with positive neutral finder	Overall Height
Final Drive	Sealed Chain	Ground Clearance

PERFORMANCE

Front Suspension / Wheel Travel 41mm telescopic fork/5.1 in

Rear Suspension / Wheel Travel Lay-down offset rear shock with linkag and adjustable preload/3.2 in

Front Tire	120/70x18	
Rear Tire	160/60x17	
Front Brakes	Single 300mm disc with twin-piston caliper	
Rear Brakes	Single 250mm disc with single-piston caliper	

	Frame Type	High-tensile steel diamond frame
), with sub-	Rake/Trail	31/4.7 in
	Overall Length	90.9 in
	Overall Width	34.6 in
l finder	Overall Height	44.5 in
_	Ground Clearance	5.1 in
	Seat Height	27.8 in
	Curb Weight	496.1 lb*
vith linkage n	Fuel Capacity	3.7 gal
	Wheelbase	62.0 in
	Color Choices	Ebony/Pearl Robotic White/Candy Steel Furnace Orange

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.