# 2022 **Z H2**





MSRP \$18,000

METALLIC GRAPHITE GRAY/METALLIC DIABLO BLACK

Uni-Trak<sup>®</sup>, Showa Gas-Charged Shock with



### **POWER**

| Engine                   | 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-<br>cooled, supercharged   |
|--------------------------|---|
| Displacement             | 998cc   |
| Bore x Stroke            | 76.0 x 55.0mm   |
| Compression<br>Ratio     | 11.2:1  |
| Maximum Torque           | 101.0 lb-ft   |
| Fuel System              | DFI, 40mm Throttle Bodies   |
| Ignition                 | TCBI w/ Digital Advance   |
| Transmission             | 6-speed dog-ring, return shift  |
| Final Drive              | Sealed chain  |
| Electronic Rider<br>Aids | Integrated Riding Modes, Kawasaki Cornering<br>Management Function (KCMF), Power Modes (3),<br>Kawasaki Launch Control Mode (KLCM), Kawasaki<br>Traction Control (KTRC), Kawasaki Launch Control<br>Mode (KLCM), Kawasaki Engine Brake Control<br>(KEBC), Kawasaki Intelligent anti-lock Brake<br>System (KIBS), Kawasaki Quick Shifter (KQS)<br>(upshift & downshift), Electronic Cruise Control |
|                          |   |

#### / Wheel Travel Adjustable Rebound Damping **Front Tire** 120/70-17 **Rear Tire** Single 260mm disc with single-piston caliper, KIBS Dual 320mm Disc w/Radial-mount Brembo M4.32 **Front Brakes** Calipers, KIBS **Rear Brakes** Single 250mm disc with single-piston caliper, KIBS

### **DETAILS**

**Rear Suspension** 

| Frame Type       | Trellis, high tensile steel                                    |
|------------------|--|
| Rake/Trail       | 24.9°/4.1in  |
| Overall Length   | 82.1 in  |
| Overall Width    | 31.9 in  |
| Overall Height   | 44.5 in  |
| Ground Clearance | 5.5 in   |
| Seat Height      | 32.7 in  |
| Curb Weight      | 529.2 lb*  |
| Fuel Capacity    | 5.0 gal  |
| Wheelbase        | 57.3 in  |
| Special Features | Rideology the App Smartphone Connectivity, TFT Instrumentation |
| Color Choices    | Metallic Graphite Gray/Metallic Diablo Black                   |

## PERFORMANCE

**Front Suspension** / Wheel Travel

Showa SFF-BP Fork with Adjustable Compression and Rebound Damping, 20 Turns Spring Preload Adjustability / 4.7 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.