## 2023 KLR<sup>®</sup>650 ADVENTURE





Let the Good Times Roll

## POWER

Engine	4-Stroke, single cylinder, DOHC
Displacement	652cc
Bore x Stroke	100.0 x 83.0mm
Compression Ratio	9.8:1
Maximum Torque	39.1 lbft. @ 4,500rpm
Fuel System	DFI® with 40mm throttle body
Ignition	CDI
Transmission	5-speed, return shift with wet multi-disc manual clutch
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

## Front BrakesSingle 300mm disc with 2-piston calipers (and<br/>ABS)Rear BrakesSingle 240mm disc with single-piston caliper<br/>(and ABS)DETAILS

Frame Type	Tubular, semi-double cradle
Rake/Trail	30.0°/4.8 in
Overall Length	89.8 in
Overall Width	38.2 in
Overall Height	57.3/55.9 in (screen hi/lo)
Ground Clearance	8.3 in
Seat Height	34.3 in
Curb Weight	487.1 lb* (ABS), 482.7 lb* (non-ABS)
Fuel Capacity	6.1 gal
Wheelbase	60.6 in
Color Choices	Cypher Camo Gray (Matte)
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, or 36 months

## PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/ 7.9 in	Со
Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/ 7.3 in	Wa Ka Pro
Front Tire	90/90-21	Plı
Rear Tire	130/80-17	



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.