## 2023 **KLR®650 TRAVELER ABS**







POWER		Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/ 7.3 in
Engine	4-Stroke, single cylinder, DOHC	Front Tire	90/90-21
Displacement	652cc	Rear Tire	130/80-17
Bore x Stroke	100.0 x 83.0mm	Front Brakes	Single 300mm disc with 2-piston calipers (and ABS)
Compression Ratio	9.8:1	Rear Brakes	Single 240mm disc with single-piston caliper and ABS
Maximum Torque	39.1 lbft. @ 4,500rpm		
Fuel System	DFI® with 40mm throttle body	DETAILS	
Ignition	CDI	Frame Type	Tubular, semi-double cradle
Transmission	5-speed, return shift with wet multi-disc manual clutch	Rake/Trail	30.0°/4.8 in
Final Drive	Sealed chain	Overall Length	89.8 in
Electronic Rider	Anti-lock Brake System (ABS)	Overall Width	38.2 in
Aids		Overall Height	57.7/56.3 in (screen hi/lo)
PERFORMANCE		Ground Clearance	8.3 in
Front	41mm telescopic fork/ 7.9 in	Seat Height	34.3 in

Front Suspension / Wheel Travel

## \*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

471.7 lb\*

6.1 gal

60.6 in

Pearl Solar Yellow

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

**Curb Weight** 

**Fuel Capacity** 

**Color Choices** 

Wheelbase

Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.

