## 2023 **KLX®110R**







## **POWER**

Engine	4-stroke single, SOHC, air-cooled
Displacement	112cc
Bore x Stroke	53.0 x 50.6mm
Compression Ratio	9.5:1
Fuel System	18mm Keihin carburetor and screw type throttle limiter on grip housing
Ignition	DC-CDI
Transmission	4-speed, return shift, automatic centrifugal and wet, multi-disc clutch
Final Drive	Chain

## PERFORMANCE

Front Suspension /	30mm hydraulic telescopic fork/4.3 in	Wheelbase
Wheel Travel		Color Choice
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/4.3 in	Warranty Kawasaki
Front Tire	2.50x14	Protection Plus™
Rear Tire	3.00x12	(optional)

Front Brakes	90mm mechanical drum, cable actuated	
Rear Brakes	110mm mechanical drum, rod actuated	
DETAILS		
Frame Type	Backbone frame, high-tensile steel	
Rake/Trail	24.8°/2.0 in	
Overall Length	61.4 in	
Overall Width	25.6 in	
Overall Height	37.6 in	
Ground Clearance	8.5 in	
Seat Height	26.8 in	
Curb Weight	167.5 lb*	
Fuel Capacity	1.0 gal	

42.3 in

Lime Green

6 Month Limited Warranty

12, 24, or 36 months

Choices

Scan with camera to view videos, key features and more.

