2023 MULE[™] 4010 TRANS4x4[®]





POWER

Engine	4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled
Displacement	617cc
Maximum Torque	34.7 lb-ft @ 2,500 rpm
Bore x Stroke	2.99x2.68 in
Compression Ratio	10:3:1
Fuel System	DFI® with 34mm Mikuni throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	23 amp

CAPABILITY

		Overall Height	75.8 in	
	Front Suspension / Wheel Travel	MacPherson Strut/3.9 in	Curb Weight	1,587.6 lb*
	Rear Suspension /	DeDion Axle/2.8 in	Wheelbase	85.2 in
Wheel Travel	Wheel Travel		Instruments	Parking brake warning light, coolant temperature
	Front Tires	23x11.00-10		warning light, 12V DC outlet, fuel gauge, hour meter
	Rear Tires	23x11.00-10	Wheel Type	Steel
	Steering	Electric Power Steering (EPS)	Color Choices	Timberline Green, Dark Royal Red
	Front Brakes	Drum	Warranty	Kawasaki STRONG 3-Year Limited Warranty
	Rear Brakes	Drum	Kawasaki	12, 24 or 36 months
	Park Brake Type	Independent, Mechanical Drum	Protection Plus™ (optional)	





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULETM 4000/4010 and MULE 4000/4010 TRANSTM Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULETM side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Ground Clearance	7.1 in
Fuel Capacity	6.3 gal
Turning Radius	12.8 ft
Cargo Bed Dimensions (LxWxH)	50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4- person)
Cargo Bed Load Capacity	800 lb (2-person) / 401 lb (4-person)
Payload Capacity	1,330 lb
Seating Capacity	2-4
Towing Capacity	1,200 lb
Lighting	(2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length

Overall Width	58.5 in
Overall Height	75.8 in
Curb Weight	1,587.6 lb*
Wheelbase	85.2 in
Instruments	Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter
Wheel Type	Steel
Color Choices	Timberline Green, Dark Royal Red

128.5 in

