
## <sup>2023</sup> MULE PRO-FX<sup>™</sup> EPS







## POWER

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Displacement	812cc
Maximum Torque	48.0 lb-ft @ 3,500 rpm
Bore x Stroke	2.83x2.62 in
<b>Compression Ratio</b>	9.5:1
Fuel System	DFI® with 34mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	75 amp

## CAPABILITY

		overall height	//.¬
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Curb Weight	1,83
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L) /8.7 in (R)	Wheelbase	92.3
wheet fravet		Instruments	Mul
Front Tires	26x9.00-12, radial		fue met
Rear Tires	26x11.00-12, radial		ind
			war
Steering	Electric Power Steering (EPS), Tilt steering		neu
Front Brakes	Dual Disc, 2 piston caliper	Miles of Towns	rem
Rear Brakes	Dual Disc, 1 piston caliper	Wheel Type	Ste
Park Brake Type	Independent, Mechanical Disc	Color Choices	Tim

Ground Clearance	10.4 in
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Cargo Bed Load Capacity	999 lb / 600.0 lb CA Model
Payload Capacity	1,616.3 lb / 1,263.5 for CA Model
Seating Capacity	3
Towing Capacity	2,000 lb
Lighting	(2) Halogen headlights.

## **DETAILS**

	Overall Length	133.3 in
	Overall Width	64.0 in
	Overall Height	77.4 in
	Curb Weight	1,830.2 lb*
	Wheelbase	92.3 in
	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
	Wheel Type	Steel
	Color Choices	Timberline Green, Bright White

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE<sup>TM</sup> PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.

