## **MULE PRO-FXR™**





\$15,299



METALLIC CARBON GRAY



## **POWER**

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement

**Maximum Torque** 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

**Compression Ratio** 9.5:1

**Fuel System** DFI® with 34mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission** 

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive** 

with differential lock

**Engine Braking** 

**Alternator Output** 75 amp

(max)

**Fuel Capacity** 7.9 gal **Turning Radius** 14.0 ft

**Cargo Bed** 

Dimensions (LxWxH)

**Cargo Bed Load** 

Capacity

**Payload Capacity** 

**Seating Capacity** 3

**Towing Capacity** 

Lighting

**DETAILS** 

2,000 lb

37.6 x 53.3 x 11.0 in

999 lb / 600.0 lb CA Model

1,616.3 lb / 1,263.5 for CA Model

(2) Halogen headlights. (2) LED headlights

CAPABILITY Front Suspension /

Double wishbone / 8.7 in

Rear Suspension / Wheel Travel

**Wheel Travel** 

Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 

27x9.00-12, radial 27x11.00-12, radial

**Rear Tires** Steering

Electric Power Steering (EPS), Tilt steering

**Front Brakes Rear Brakes** 

Dual Disc, 2 piston caliper Dual Disc, 1 piston caliper

**Park Brake Type** 

Independent, Mechanical Disc

**Ground Clearance** 

10.8 in

**Overall Length** 121.5 in

**Overall Width** 64.0 in

**Overall Height** 77.2 in

**Curb Weight** 1,768.4 lb\*

79.7 in

Wheelbase

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type

**Additional Features** Roof, Rear Bumper, Contoured Two-Tone Bench Seat

**Color Choices** Metallic Carbon Gray

Warranty Kawasaki STRONG 3-Year Limited Warranty

**Kawasaki Protection** 12, 24 or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471