MULE PRO-FXT™ EPS





MSRP **\$15,899**



BRIGHT WHITE



TIMBERLINE GREEN



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output 75 amp

(max)

Ground Clearance

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

person)

10.2 in

Cargo Bed Load Capacity

Payload Capacity

1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity

3-person (1 row), 6 person (2 row)

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Towing Capacity

2,000 lb

Lighting

(2) Halogen headlights.

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial

26x11.00-12, radial

Rear Tires
Steering

Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type

Independent, Mechanical Disc

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1,911.7 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Wheel Type Steel

Color Choices

Timberline Green, Bright White

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.