MULE PRO-FXT™ RANCH EDITION





\$18,599



METALLIC TITANIUM



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio

DFI® with 34mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

75 amp

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires

26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Independent, Mechanical Disc Park Brake Type

Ground Clearance 10.0 in

Turning Radius 16.0 ft

Fuel Capacity

Cargo Bed Load

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

person)

Capacity

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

7.9 gal

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2.000 lb

(2) Halogen headlights. (2) LED headlights Lighting

DETAILS

Overall Length 135.6 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1,971.3 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type Alloy

Additional Features Roof, WARN® VRX 45 Winch, Premium Seats, Front Bumper

Plates

Color Choices Metallic Titanium

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.