2023 **MULE PRO-FXT**[™]







SUPER BLACK

10.2 in



POWER

| Engine | 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas |
|----------------------------|-------------------------------------------------------------------------------|
| Displacement | 812cc |
| Maximum Torque | 48.0 lb-ft @ 3,500 rpm |
| Bore x Stroke | 2.83x2.62 in |
| Compression Ratio | 9.5:1 |
| Fuel System | DFI® with 34mm throttle body |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking | Yes |
| Alternator Output (max) | 75 amp |

| Fuel Capacity | 7.9 gal |
|---------------------------------|-------------------------------------------------------------------------|
| Turning Radius | 16.0 ft |
| Cargo Bed Dimensions (LxWxH) | 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6- person) |
| Cargo Bed Load Capacity | 999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model |
| Payload Capacity | 1,616.3 lb / 1,263.5 lb CA Model |
| Seating Capacity | 3-person (1 row), 6 person (2 row) |
| Towing Capacity | 2,000 lb** |
| Lighting | (2) Halogen headlights. |

DETAILS

Ground Clearance

| Overall Length | 133.3 in |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Overall Width | 64.0 in |
| Overall Height | 77.6 in |
| Curb Weight | 1,887.5 lb* |
| Wheelbase | 92.3 in |
| Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Wheel Type | Steel |
| Color Choices | Super Black |
| Warranty | Kawasaki STRONG 3-Year Limited Warranty |
| Kawasaki Protection Plus™ (optional) | 12, 24 or 36 months |

CAPABILITY

| Front Suspension / Wheel Travel | Double wishbone/8.7 in |
|------------------------------------|----------------------------------------|
| Rear Suspension / Wheel Travel | Double wishbone/8.5 in (L) /8.7 in (R) |
| Front Tires | 26x9.00-12, radial |
| Rear Tires | 26x11.00-12, radial |
| Steering | Rack-and-pinion |
| Front Brakes | Dual Disc, 2 piston caliper |
| Rear Brakes | Dual Disc, 1 piston caliper |
| Park Brake Type | Independent, Mechanical Disc |
| | |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULETM side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.