
²⁰²³ MULE PRO-MX[™] EPS CAMO









| Engine | 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled |
|----------------------------|---|
| Displacement | 695cc |
| Maximum Torque | 42.7 lb-ft @ 5,000 rpm |
| Bore x Stroke | 102.0 x 85.0 mm |
| Compression Ratio | 10.3:1 |
| Fuel System | DFI® with 44mm throttle body |
| Transmission | Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R) |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock |
| Engine Braking | Yes |
| Alternator Output (max) | 35.7 amp |

| Ground Clearance | 10.6 in |
|---------------------------------|--|
| Fuel Capacity | 9.5 gal |
| Turning Radius | 14.0 ft |
| Cargo Bed Dimensions (LxWxH) | 33.4 x 44.1 x 9.1 in |
| Cargo Bed Load Capacity | 699 lb / 600 lb CA Model |
| Payload Capacity | 1,200 lb |
| Seating Capacity | 2 |
| Towing Capacity | 1,500 lb |
| Lighting | (2) Halogen headlights. (2) LED headlights |

Independent, Mechanical Disc

DETAILS

Park Brake Type

| | | Overall Length | 110.0 in |
|-----------------------------------|--|---------------------|---|
| CAPABILITY | | Overall Width | 60.0 in |
| Front Suspension / | Double wishbone/8.6 in | Overall Height | 75.8 in |
| Wheel Travel | | Curb Weight | 1,598.6 lb* |
| Rear Suspension / Wheel Travel | Double wishbone/9.1 in | Wheelbase | 78.9 in |
| Front Tires | 25x10.00-12, radial | Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, |
| Rear Tires | 25x10.00-12, radial | | 2WD/4WD indicator, water temperature warning indicator, |
| Steering | Electric Power Steering (EPS), Tilt steering | | EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps |
| Front Brakes | Dual Disc, 2 piston caliper | Wheel Type | Steel |
| Rear Brakes | Dual Disc, 1 piston caliper | wheet type | Steet |
| | | Additional Features | Roof |
| | | Color Choices | TrueTimber [®] HTC Green |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. ™/® © 2019 TrueTimber Outdoors Holding Company, LLC. Manufactured and/or distributed under official license by Kawasaki Motors Corp., U.S.A. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.