MULE PRO-MX™ EPS





\$13,599



FIRECRACKER RED



TIMBERLINE GREEN



10.6 in

9.5 gal

14.0 ft

1,200 lb

33.4 x 44.1 x 9.1 in

699 lb / 600 lb CA Model

POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement

Maximum Torque 42.7 lb-ft @ 5,000 rpm

102.0 x 85.0 mm Bore x Stroke

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

Seating Capacity Towing Capacity

1,500 lb

Lighting

Ground Clearance

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Dimensions (LxWxH)

Cargo Bed

Capacity

(2) Halogen headlights. (2) LED headlights

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in **Overall Height** 74.4 in **Curb Weight** 1,587.6 lb* Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Steel

Color Choices Timberline Green, Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection 12, 24 or 36 months Plus™ (optional)

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.6 in

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

25x8.00-12, radial

Front Tires Rear Tires

25x10.00-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type

Independent, Mechanical Disc

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.