²⁰²³ MULE SX[™] 4x4 XC LE FI





Ground Clearance

Fuel Capacity

Turning Radius

Dimensions (LxWxH) Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

Cargo Bed

Capacity

Lighting

DETAILS

METALLIC ONYX BLACK

8.1 in

4.2 gal

11.8 ft

399 lb

884 lb

1,100 lb**

(4) LED headlights, tail/brake lights

2

35.6 x 40.9 x 9.6 in



Let the Good Times Roll

POWER

Engine	4-stroke, single-cylinder, OHV, air-cooled
Displacement	401cc
Maximum Torque	21.4 lb-ft @ 2,400 rpm
Bore x Stroke	3.23x2.99 in
Compression Ratio	8.6:1
Fuel System	Fuel injection
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output	22.9 amp

(max) Overall Length 106.7 in CAPABILITY Overall Width 52.6 in Sector Summing (s) Noverall Height 75.0 in				
GAPABILITY Overall Height 75.0 in	Overall Length 106.7 in	erall Length 106.7 in	0	(max)
Overall Height 75.0 in	Overall Width 52.6 in	erall Width 52.6 in	0	CAPABILITY
Front Surgery in J. Marchanger Chard (2.4 in	Overall Height 75.0 in	erall Height 75.0 in	0	
Front Suspension / Wheel Travel MacPherson Strut/3.1 in Curb Weight 1,098.1 lb*	Curb Weight 1,098.1 lb*	rb Weight 1,098.1 lb*	Strut/3.1 in	Front Suspension / Wheel Travel
Rear Suspension / Unit Swingarm/3.1 in Wheelbase 70.1 in	Wheelbase 70.1 in	eelbase 70.1 in	m/3.1 in W	Rear Suspension /
Wheel Travel Instruments Fuel gauge, hour meter, oil temp light, parking brake light	Instruments Fuel gauge, hour meter, oil temp ligh	truments Fuel gauge, hour meter, oil temp light, parkin		
Front Tires 26x9.00-12 Wheel Type Steel	Wheel Type Steel	eel Type Steel	W	Front Tires
Rear Tires 26x9.00-12 Additional Features Roof, Under Seat Storage, LED Headlights, Painted Bod	Additional Features Roof, Under Seat Storage, LED Head	ditional Features Roof, Under Seat Storage, LED Headlights, Pa	А	Rear Tires
Steering Rack-and-pinion Panels	Panels	Panels	nion	Steering
Front Brakes Drum Color Choices Metallic Onyx Black	Color Choices Metallic Onyx Black	or Choices Metallic Onyx Black	с	Front Brakes
Rear Brakes Drum				Rear Brakes
Park Brake Type Independent, Mechanical Drum	n		, Mechanical Drum	Park Brake Type



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Requires optional hitch

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.