## TERYX KRX® 1000 eS





# \$22,699



ICE GRAY/METALLIC ONYX BLACK



#### **POWER**

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

**Maximum Torque** 76.7 lb-ft @ 7.000 rpm

Bore x Stroke 92.0 x 75.1mm

**Compression Ratio** 

DFI® with two 50mm throttle bodies **Fuel System** 

Ignition TCBI with Electronic Advance

**Starting System** 

Transmission Automatic CVT with centrifugal clutch (H.L.N.R)

**Final Drive** Selectable 2WD/4WD with locking front differential, shaft

**Engine Braking** Yes 14.6 x 33.1 x 9.1 in

**Cargo Bed Load Capacity Payload Capacity** 781 lh **Seating Capacity** 

**Towing Capacity** 

Clearance/Maximum **Ground Clearancet** 

14.0 in (std) / 14.4 in (max)

### **CAPABILITY**

Front Suspension /

Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks

Rear Suspension / Wheel Travel

Rear Brakes

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal

KECS controlled compression damping/21.1 in

**Front Tires** Maxxis® Carnivore 31 x 10.00R15 8PR Maxxis® Carnivore 31 x 10 00R15 8PR Rear Tires

Steering **Front Brakes** Dual hydraulic discs with two-piston calipers

**Ground Clearance** 

**Fuel Capacity Turning Radius** 20.3 ft

with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in

Bypass shocks with piggyback reservoir, fully adjustable preload, and

Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with single-piston calipers

14.4 in (max), 14.0 in (std)

10.6 gal

**Cargo Bed Dimensions** 

351 lb N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

**Standard Ground** 

### **DETAILS**

Frame Ladder type, tubular steel

**Overall Length** 132.1 in **Overall Width** Overall Height 77.0 in

**Curb Weight** 1,944.8 lb\* / 1,947.0 lb\* CA Model

Wheelbase

Instruments Multi-function digital meter with bar-style tachometer (2 display

options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp.

Wheel Type Alloy with bead-lock wheels

**Additional Features** Roof, Front Bumper

**Color Choices** Ice Gray/Metallic Onyx Black

Warranty 6 months

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

tMaximum ground clearance is measured at maximum pre-load suspension setting. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.