## TERYX KRX°4 1000 eS





MSRP **\$25,499** 





## **POWER**

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 9999

Maximum Torque 76.7 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

Fuel System DFI® with two 50mm throttle bodies

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

## **CAPABILITY**

Front Suspension / Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass Wheel Travel shocks with piggyback reservoir, fully adjustable preload, and

KECS controlled compression damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve
Wheel Travel Internal Bypass shocks with piggyback reservoir, fully adjustable

Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 15.2 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal
Turning Radius 23.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in

Cargo Bed Load

Capacity

pad Capacity 1,001 lb

Payload Capacity

4

Seating Capacity

Towing Capacity

N/A

351 lb

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

## DETAILS

Frame Ladder type, tubular steel

Overall Length 157.3 in

Overall Width 68.1 in

Overall Height 76.2 in

Curb Weight 2,105.8 lb\* / 2,108.0 lb\* CA Model

Wheelbase 125.8 in

nstruments Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator

(L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp.

EPS warning lamp, and CVT belt warning lamp.

Wheel Type Alloy wheel

Color Choices Metallic Flat Raw Graystone/Candy Steel Furnace Orange

Warranty 6 Month Limited Warranty

Kawasaki Protection Plus™ (optional)

12, 24, or 36 months

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.