TERYX® S LE





\$14,999



METALLIC ELECTRIC TURQUOISE/SUPER BLACK



NEON RED/SUPER BLACK



POWER

4-stroke, SOHC, 4-valve V-twin, liquid-cooled **Engine**

Displacement 783cc

47.0 lb-ft@ 5,500 rpm Maximum Torque

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

DFI® with two 36mm Mikuni throttle bodies **Fuel System**

Ignition TCBI with Electronic Advance

Starting System Electric

Automatic CVT with centrifugal clutch (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes **Fuel Capacity** 7.9 gal

Cargo Bed Dimensions 27.6 x 43.3 x 10.4 in

(LxWxH)

Cargo Bed Load

600 lb

17.7 ft

Capacity

Turning Radius

Payload Capacity

Seating Capacity Towing Capacity

1,300 lb

1,100 lb

Lighting

(4) LED headlights, (2) incandescent taillights, incandescent

stoplight

Standard Ground Clearance/Maximum **Ground Clearancet**

11.2 in / 12.2 in

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.7

Rear Suspension / Wheel Travel

Front Tires

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in Maxxis® 27 x 9-14

Rear Tires Maxxis® 27 x 11-14

Electric Power Steering (EPS) / rack-and-pinion **Steering**

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

Ground Clearance 11.2 in / 12.2 in

DETAILS

Frame Steel Tube Double-X Reinforcement

Overall Length 118.1 in

Overall Width 62.2 in

Overall Height 78.5 in

Curb Weight 1.596.4 lb*

Wheelbase 88.2 in

Multi-function digital meter with speedometer, fuel gauge, Instruments

clock, hour meter, odometer, dual trip meter and parkingbrake indicator, R/N/P/4WD, water temp and low-oil-pressure

indicators

Wheel Type Alloy

Additional Features Roof

Color Choices Neon Red/Super Black, Metallic Electric Turquoise/Super





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.