

2023

TERYX® S LE

Kawasaki
Let the Good Times Roll®



- MSRP
\$14,999
- METALLIC ELECTRIC TURQUOISE/SUPER BLACK
- NEON RED/SUPER BLACK



POWER		DETAILS	
Engine	4-stroke, SOHC, 4-valve V-twin, liquid-cooled	Cargo Bed Dimensions (LxWxH)	27.6 x 43.3 x 10.4 in
Displacement	783cc	Cargo Bed Load Capacity	600 lb
Maximum Torque	47.0 lb-ft@ 5,500 rpm	Payload Capacity	1,100 lb
Bore x Stroke	85.0 x 69.0mm	Seating Capacity	2
Compression Ratio	10.7:1	Towing Capacity	1,300 lb
Fuel System	DFI® with two 36mm Mikuni throttle bodies	Lighting	(4) LED headlights, (2) incandescent taillights, incandescent stoplight
Ignition	TCBI with Electronic Advance	Standard Ground Clearance/Maximum Ground Clearance†	11.2 in / 12.2 in
Starting System	Electric		
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft		
Engine Braking	Yes		
CAPABILITY		Frame	Steel Tube Double-X Reinforcement
Front Suspension / Wheel Travel	Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.7 in	Overall Length	118.1 in
Rear Suspension / Wheel Travel	Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.0 in	Overall Width	62.2 in
Front Tires	Maxxis® 27 x 9-14	Overall Height	78.5 in
Rear Tires	Maxxis® 27 x 11-14	Curb Weight	1,596.4 lb*
Steering	Electric Power Steering (EPS) / rack-and-pinion	Wheelbase	88.2 in
Front Brakes	Dual hydraulic discs with two-piston calipers	Instruments	Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and low-oil-pressure indicators
Rear Brakes	Sealed, oil-bathed, multi-disc	Wheel Type	Alloy
Ground Clearance	11.2 in / 12.2 in	Additional Features	Roof
Fuel Capacity	7.9 gal	Color Choices	Neon Red/Super Black, Metallic Electric Turquoise/Super Black
Turning Radius	17.7 ft	Warranty	Kawasaki Strong 3-Year Limited Warranty
		Kawasaki Protection Plus™ (optional)	12, 24, or 36 months

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.