# Z H2 SE





### MSRP **\$20,700**



METALLIC MATTE GRAPHENESTEEL GRAY/EBONY/ MIRROR COATED BLACK



#### **POWER**

Engine 4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled,

supercharged

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 11.2:1

Maximum Torque 101.0 lb-ft

Fuel System DFI® with 40mm throttle bodies

**Ignition** TCBI with Digital Advance

Transmission 6-speed dog-ring, return shift

Final Drive Sealed chain

Electronic Rider

Kawasaki Electronic Control Suspension (KECS) with Showa Skyhook Technology, KECS Linked Integrated Riding Modes, Kawasaki Cornering Management Function (KCMF), Power Modes (3), Kawasaki Launch Control Mode (KLCM), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Engine Brake Control (KEBC), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS) (upshift & downshift), Electronic Cruise Control

## **PERFORMANCE**

Front Suspension / Wheel Travel

Showa SFF-BP Fork with KECS Compression and KECS Rebound Damping, plus Manual Spring Preload Adjustability/4.7 in

Rear Suspension /

Wheel Travel

Uni-Trak®, Showa Gas-Charged Shock with KECS Compression and KECS Damping, plus Manual Spring Preload Adjustability/5.3 in Front Tire 120/70-17

**Rear Tire** 190/55-17

Front Brakes Dual 320mm Disc w/ Radial-mount Brembo M4.32

Calipers, Kawasaki Intelligent anti-lock Brake System

(KIBS)

**Rear Brakes** Single 260mm disc with single-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

## **DETAILS**

Frame Type Trellis, high tensile steel

Rake/Trail 24.9°/4.1in

Overall Length 82.1 in

Overall Width 31.9 in

Overall Height 44.5 in

**Ground Clearance** 5.5 in

Seat Height 32.7 in

Curb Weight 531.4 lb\*

Fuel Capacity 5.0 gal

Wheelbase 57.3 in

Special Features Smartphone Connectivity via RIDEOLOGY THE APP, TFT

Instrumentation

Color Choices Metallic Matte Graphenesteel Gray/Ebony/Mirror

Coated Black

Warranty 12 Month Limited Warranty

**Kawasaki** 12, 24, 36 or 48 months

stability/5.3 in Protection Plus™ (optional)



