## 2023 **Z125 PR0**







## **POWER**

| Engine               | 4-stroke, 1 cylinder, SOHC, 2-valve, air-<br>cooled |
|----------------------|---|
| Displacement         | 125cc   |
| Bore x Stroke        | 56.0 x 50.6mm                                       |
| Compression<br>Ratio | 9.8:1   |
| Maximum<br>Torque    | 7.1 lb-ft @ 6,000 rpm                               |
| Fuel System          | DFI® with 24mm throttle bodies                      |
| Ignition             | TCBI with Electronic Advance                        |
| Transmission         | 4-speed, return shift                               |
| Final Drive          | Sealed chain  |

| Front Tire   | 100/90-12                     |
|--------------|-------------------------------|
| Rear Tire    | 120/70-12                     |
| Front Brakes | Single 200mm petal-style disc |
| Rear Brakes  | Single 184mm petal-style disc |

## **DETAILS**

| 9.8:1   |                       |   |
|---|-----------------------|---|
|   | Frame Type            | Backbone  |
| 7.1 lb-ft @ 6,000 rpm                                 | Rake/Trail            | 26.0°/2.7 in  |
| DFI® with 24mm throttle bodies                        | <b>Overall Length</b> | 66.9 in   |
| TCBI with Electronic Advance<br>4-speed, return shift | Overall Width         | 29.5 in   |
|   | Overall Height        | 39.6 in   |
| Sealed chain  | Ground<br>Clearance   | 6.1 in  |
| ANCE  | Seat Height           | 31.7 in   |
| ANOL  | Curb Weight           | 224.8 lb*   |
| Telescopic fork/3.9 in                                | Fuel Capacity         | 2.0 gal   |
|   | Wheelbase             | 46.3 in   |
| Swingarm, single shock/4.1 in                         | Color Choices         | Firecracker Red, Pearl Matte Sage Green,<br>Metallic Ocean Blue |
|   |                       |   |

## PERFORMANCE

Front Suspension /

Wheel Travel

Rear Suspension / Wheel Travel

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.