

2023
Z650



- MSRP NON-ABS

\$7,749
- MSRP ABS

\$8,249
- METALLIC MATTE GRAPHENESTEEL GRAY/EBONY
- METALLIC SPARK BLACK/METALLIC FLAT SPARK BLACK



POWER		Rear Tire	160/60 ZR17
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Front Brakes	Dual 300mm petal-style discs with two-piston calipers (and ABS)
Displacement	649cc	Rear Brakes	Single 220mm petal-style disc (and ABS)
Bore x Stroke	83.0 x 60.0mm	DETAILS	
Compression Ratio	10.8:1	Frame Type	Trellis, high tensile steel
Maximum Torque	48.5 lb-ft @ 6,500 rpm	Rake/Trail	24.0° / 3.9 in
Fuel System	DFI® with Keihin 36mm throttle bodies	Overall Length	80.9 in
Ignition	TCBI with Electronic Advance	Overall Width	30.1 in
Transmission	6-speed, return shift	Overall Height	41.9 in
Final Drive	Sealed chain	Ground Clearance	5.1 in
Electronic Rider Aids	Kawasaki TRaction Control (KTRC - 2 Modes)	Seat Height	31.1 in
PERFORMANCE		Curb Weight	412.3 lb* (ABS), 410.1 lb* (non-ABS)
Front Suspension / Wheel Travel	Telescopic fork/4.9 in	Fuel Capacity	4.0 gal
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable preload, swingarm/5.1 in	Wheelbase	55.5 in
Front Tire	120/70 ZR17	Special Features	Rideology the App Smartphone Connectivity, TFT Instrumentation
		Color Choices	Metallic Spark Black/Metallic Flat Spark Black, Metallic Matte Graphenesteel Gray/Ebony

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.