2024 **KLR®650**





MSRP NON-ABS \$6,899





PEARL CRYSTAL WHITE/METALLIC CARBON GRAY



FIRECRACKER RED/METALLIC CARBON GRAY



POWER		Front Tire	90/90-21
		Rear Tire	130/80-17
Engine	4-Stroke, single cylinder, DOHC	Front Brakes	Single 300mm disc with 2-piston calipers (and
Displacement	652cc		ABS)
Bore x Stroke	100.0 x 83.0mm	Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)
Compression	9.8:1		
Ratio		DETAILS	
Maximum	39.1 lb-ft @ 4,500rpm	DEIMILO	
Torque		Frame Type	Tubular, semi-double cradle
Fuel System	DFI® with 40mm throttle body	Rake/Trail	30.0°/4.8 in
Ignition	CDI	Overall Length	89.8 in
Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Width	38.2 in
Final Drive	Sealed chain	Overall Height	57.7/56.3 in (screen hi/lo)
Electronic Rider Aids	Anti-lock Brake System (ABS)	Ground Clearance	8.3 in
		Seat Height	34.3 in
PERFORMANCE		Curb Weight	460.6 lb* (ABS), 456.2 lb* (non-ABS)

Front Suspension / Wheel Travel 41mm telescopic fork/ 7.9 in

Rear Suspension / Wheel Travel Uni-Trak[®] single shock with adjustable rebound damping and adjustable spring preload/8.0 in

Color Choices Pearl Crystal White/Metallic Carbon Gray, Firecracker Red/Metallic Carbon Gray

6.1 gal

60.6 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Fuel Capacity

Wheelbase

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.