

2024

KLR® 650 S

Kawasaki

Let the Good Times Roll®

MSRP NON-ABS
\$6,899MSRP ABS
\$7,199

PEARL CRYSTAL WHITE/METALLIC CARBON GRAY



FIRECRACKER RED/METALLIC CARBON GRAY



POWER

Engine	4-Stroke, single cylinder, DOHC
Displacement	652cc
Bore x Stroke	100.0 x 83.0mm
Compression Ratio	9.8:1
Maximum Torque	39.1 lb.-ft. @ 4,500rpm
Fuel System	DFI® with 40mm throttle body
Ignition	CDI
Transmission	5-speed, return shift with wet multi-disc manual clutch
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/ 6.7 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/7.0 in

Front Tire	90/90-21
Rear Tire	130/80-17
Front Brakes	Single 300mm disc with 2-piston calipers (and ABS)
Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)

DETAILS

Frame Type	Tubular, semi-double cradle
Rake/Trail	29.5° /4.6 in
Overall Length	88.8 in
Overall Width	38.2 in
Overall Height	56.3/54.9 in (screen hi/lo)
Ground Clearance	7.3 in
Seat Height	32.1 in
Curb Weight	460.6 lb* (ABS), 456.2 lb* (non-ABS)
Fuel Capacity	6.1 gal
Wheelbase	59.6 in
Color Choices	Pearl Crystal White/Metallic Carbon Gray, Firecracker Red/Metallic Carbon Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.