## KX<sup>™</sup>250









LIME GREEN



## **POWER**

4-stroke single, DOHC, liquid-cooled **Engine** 

Displacement 249cc

**Bore x Stroke** 78.0 x 52.2mm

Compression

Ratio

14.1:1

DFI® with 44mm Keihin throttle body and **Fuel System** 

dual injectors

Ignition Digital CDI

**Transmission** 5-speed, return shift, with wet multi-disc

manual clutch

**Final Drive** Chain

**Electronic Rider** 

**Aids** 

Launch Control Mode

## **PERFORMANCE**

**Front** Suspension / **Wheel Travel** 

48mm inverted telescopic coil-spring fork with 23-way compression damping and 20way rebound damping /12.4 in

Rear Suspension / **Wheel Travel** 

Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.4 in

**Front Tire** 80/100-21

**Rear Tire** 110/90-19

**Front Brakes** Single semi-floating 270mm Braking petal

disc with dual-piston caliper

**Rear Brakes** Single 240mm Braking petal disc with

single-piston caliper

## **DETAILS**

Aluminum perimeter **Frame Type** 

Rake/Trail 28.0° / 4.6 in

**Overall Length** 86.2 in

**Overall Width** 32.3 in

**Overall Height** 50.0 in

13.6 in Ground Clearance

**Seat Height** 37.8 in

**Curb Weight** 227.6 lb\* without fuel / 237.7 lb\*

**Fuel Capacity** 1.64 gal

Wheelbase 58.5 in

**Color Choices** Lime Green



