MULE PRO-FXT[™] 1000 LE





\$18,799



METALLIC SIERRA BLUE



METALLIC ONYX BLACK



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Fuel System DFI® with 38mm throttle body

10.1:1

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 90 amp

(max)

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Capacity

Cargo Bed Load Payload Capacity

Dimensions (LxWxH)

1,616.3 lb / 1,263.5 lb CA Model

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/11.0 in **Wheel Travel**

Double wishbone/10.1 in Rear Suspension / **Wheel Travel**

Front Tires 26 x 9.00-12, radial **Rear Tires** 26 x 11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper **Park Brake Type** Independent, Mechanical Disc

DETAILS

Overall Length 135.8 in **Overall Width** 64.0 in

Overall Height 80.9 in

Curb Weight 1,913.9 lb* / 1,916.1 lb* CA Model

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Wheel Type

Additional Features Roof, Additional Front Cup Holders

Color Choices Metallic Onyx Black, Metallic Sierra Blue

Scan with camera to view videos, key features and more.

