MULE PRO-FXT™ 1000 LE CAMO





\$18,899



TRUETIMBER® STRATA



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking

90 amp **Alternator Output**

(max)

Front Tires

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Capacity

Cargo Bed Load

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/11.0 in **Wheel Travel**

Double wishbone/10.1 in Rear Suspension /

Wheel Travel

Rear Tires 26 x 11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

26 x 9.00-12, radial

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Park Brake Type Independent, Mechanical Disc

DETAILS

Overall Length 135.8 in **Overall Width** 64.0 in

Overall Height 80.9 in

Curb Weight 1,922.8 lb* / 1,925 lb* CA Model

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Wheel Type

Additional Features Roof, Additional Front Cup Holders

Color Choices TRUETIMBER® STRATA

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.