2024 NINJA® ZX[™]-14R 40th ANNIVERSARY EDITION ABS









LIME GREEN/PEARL CRYSTAL WHITE/BLUE



POWER

Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled
Displacement	1,441cc
Bore x Stroke	84.0 x 65.0mm
Compression Ratio	12.3:1
Fuel System	DFI® with 44mm Mikuni throttle bodies (4)
Ignition	TCBI, battery powered & Electronic Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC), Power Modes, Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in
Rear Suspension / Wheel Travel	Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride height/4.9 in

Front Tire	120/70ZR17
Rear Tire	190/50ZR17
Front Brakes	Dual semi-floating 310mm Brembo discs with dual radial-mounted Brembo 4-piston M50 monobloc calipers and ABS
Rear Brakes	Single 250mm disc with twin-piston caliper and ABS

DETAILS

•	Frame Type	Aluminum monocoque
	Rake/Trail	23.0°/3.7 in
	Overall Length	85.4 in
	Overall Width	30.3 in
	Overall Height	46.1 in
	Ground Clearance	4.9 in
	Seat Height	31.5 in
	Curb Weight	593.1 lb*
	Fuel Capacity	5.8 gal
	Wheelbase	58.3 in
	Color Choices	Lime Green/Pearl Crystal White/Blue



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.