# 2024 NINJA<sup>®</sup> ZX<sup>™</sup>-4RR KRT EDITION ABS







### POWER

Engine	4-stroke, In-Line Four, OHC, 16-valve, liquid- cooled
Displacement	399сс
Bore x Stroke	57.0 x 39.1mm
Compression Ratio	12.3:1
Fuel System	DFI® with 34mm throttle valves (4)
Ignition	Digital
Transmission	6-speed, manual, return shift
Final Drive	Chain
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock Brake System (ABS)

# Front Tire110/70-17Rear Tire160/60-17Front BrakesDual 290mm discs, ABSRear BrakesSingle 220mm disc, ABS

#### **DETAILS**

MSRP

Frame Type	Trellis, high-tensile steel
Rake/Trail	23.5°/3.8 in
Overall Length	78.3 in
Overall Width	30.1 in
Overall Height	43.7 in
Ground Clearance	5.3 in
Seat Height	31.5 in
Curb Weight	414.5 lb*
 Fuel Capacity	4.0 gal
Wheelbase	54.3 in
Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLOGY THE APP
Color Choices	Lime Green/Ebony

## PERFORMANCE

Front<br/>Suspension /<br/>Wheel Travel37mm inverted fork with SFF-BP internals<br/>and spring preload adjustability/4.7 inRearHorizontal Back-link, BFRC lite gas charge

Suspension / Wheel Travel Horizontal Back-link, BFRC lite gas charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.