

2024

# NINJA<sup>®</sup> ZX<sup>™</sup> -6R

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



MSRP NON-ABS  
**\$11,399**

MSRP ABS  
**\$12,399**



METALLIC FLAT SPARK BLACK/EBONY



PEARL ROBOTIC WHITE/METALLIC GRAPHITE GRAY



## POWER

Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled
Displacement	636cc
Bore x Stroke	67.0 x 45.1mm
Compression Ratio	12.9:1
Fuel System	DFI <sup>®</sup> with 38mm Keihin throttle bodies (4) and oval sub-throttles
Ignition	TCBI with Electronic Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki Traction Control (KTRC), Power Modes (Full/Low), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Kawasaki Quick Shifter (KQS) (upshift only)

Rear Tire	180/55 ZR17
Front Brakes	Dual semi-floating 310mm discs with dual radial-mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Rear Brakes	Single 220mm petal discs with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)

## PERFORMANCE

Front Suspension / Wheel Travel	41mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs/4.7 in
Rear Suspension / Wheel Travel	Bottom-link Uni-Trak <sup>®</sup> with gas-charged shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring preload/5.9 in
Front Tire	120/70 ZR17

## DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	23.5° / 4.0 in
Overall Length	79.7 in
Overall Width	28.0 in
Overall Height	43.3 in
Ground Clearance	5.1 in
Seat Height	32.7 in
Curb Weight	436.6 lb* (ABS), 432.2 lb* (non-ABS) 50-State Model, 434.4 lb* (ABS), 430.0 lb* (non-ABS) 49-State Model
Fuel Capacity	4.5 gal
Wheelbase	55.1 in
Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP
Color Choices	Lime Green/Ebony

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](http://Kawasaki.com) for full product details.